

EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

Document 7)
(English abstract of
JP-A-11-38201)

PUBLICATION NUMBER : 11038201
PUBLICATION DATE : 12-02-99

APPLICATION DATE : 23-07-97
APPLICATION NUMBER : 09197615

APPLICANT : FUJI PHOTO FILM CO LTD;

INVENTOR : YASUDA TOMOKAZU;

INT.CL. : G02B 1/11 B05D 5/06 B32B 7/02 B32B 9/00 G02F 1/1335

TITLE : ANTIREFLECTION FILM AND IMAGE DISPLAY DEVICE USING THE SAME

ABSTRACT : PROBLEM TO BE SOLVED: To improve the film strength and durability of a low-refractive index layer and to obtain high anti-reflection efficiency by strictly regulating the film thicknesses and refractive indices of respectively layers.

SOLUTION: A middle-refractive index layer, high-refractive index layer and low-refractive index layer are successively formed from a base material side toward an air surface on the front surface of a transparent base material. The middle-refractive index layer contains the metal oxide selected from aluminum, etc., and the high-refractive index layer contains titanium oxide. The low-refractive index layer contains particulates consisting of a polymer of a fluorine-contained monomer and microvoids which do not scatter light. The refractive indices and film thicknesses of the respective layers are in ranges of the middle-refractive index layer: $n_3=1.60\sim1.70$, $h\lambda/4 \times 0.8 < n_3 d_3 < h\lambda/4 \times 1.2$, the high-refractive index layer: $n_2=1.90$ to 2.20 , $h\lambda/4 \times 0.8 < n_2 d_2 < h\lambda/4 \times 1.2$, the low-refractive index layer: $n_1=1.37$ to 1.46 , $h\lambda/4 \times 0.8 < n_1 d_1 < h\lambda/4 \times 1.2$, where (h) and (k) respectively denote 1, 2 or 3 and (n) and (d) respectively denote the refractive indices and layer thicknesses (nm) of the respectively refractive index layers.

COPYRIGHT: (C)1999,JPO